



DISCRETE VALVE CONTROLLERS

POSITION MONITORING AND CONTROL OF AUTOMATED ON/OFF VALVES

- Suitable for use on rotary and linear applications
- Certified for use in all hazardous areas
- Integrated solutions (bus + sensors + pilot)
- Technology leadership in fieldbus networks



TOPWORK


EMERSON
Process Management



TopWorx™, a division of Emerson™ Process Management, is a global leader in valve control and position sensing for the process industries. Our solutions enable plants, platforms, and pipelines to manage and control operations more intelligently and efficiently under the most demanding and extreme conditions.

GLOBAL TECHNOLOGY LEADERSHIP

TopWorx technology advancements are at the forefront of innovation in the process automation industry. TopWorx uses wireless technologies and fieldbus protocols such as FOUNDATION Fieldbus, DeviceNet, AS-Interface, Profibus, and HART to reduce installation costs and enable predictive maintenance.



GLOBAL HAZARDOUS AREA CERTIFICATIONS

In addition to high temperature (204°C), cold temperature (-50°C), and sub-sea (6,800 meters) applications, TopWorx products are suitable for use in Flame-proof/Explosion Proof, Non-Incendive, Intrinsically Safe hazardous areas with IECEx, ATEX, GOST, InMetro, UL, CSA, KOSHA, and NEPSI certifications.



GLOBAL SERVICE & SUPPORT

With company locations in the United States, United Kingdom, South Africa, Bahrain, and Singapore, TopWorx is strategically positioned to provide outstanding support. In addition, over 200 Certified Product Partners throughout the world are available to provide competent local support when needed.



WWW.TOPWORX.COM

Visit www.topworx.com for comprehensive information on our company, capabilities, and products – including model numbers, data sheets, specifications, dimensions, and certifications.



Valvetop™ discrete valve controllers enable automated on/off valves to communicate via FOUNDATION Fieldbus, DeviceNet, AS-Interface, Profibus, and HART protocols. They attach to all rotary and linear valves and actuators, operate in the most demanding environmental conditions, and carry a variety of hazardous area certifications.

Discrete Valve Controllers for:

- Any bus network
- Any hazardous area
- Any valve or actuator
- Anywhere in the world

TopWorx Valvetop valve control solutions deliver on today's new customer requirements. With the Valvetop program, customers enjoy:

- A complete line of valve controllers and monitors for every protocol, application, environment, and hazardous area.
- The world's leading selection of valve networking products, including FOUNDATION Fieldbus, DeviceNet, AS-Interface, Profibus, and HART.
- 'GO Switch Inside™', the most reliable and durable valve position sensor on the planet.
- Quality products with global agency approvals including IECEx, ATEX, CE, UL, CSA, FM as well as NEPSI, KOSHA, InMetro, and GOST.
- The unmatched process experience and bus networking expertise of TopWorx, the leading provider of valve control and position sensing solutions for the process industries.

VALVETOP™ D-SERIES

World-Class Discrete Valve Controllers with the Highest Technology Available

Valvetop D-Series discrete valve controllers are certified for use in every world area. They carry IECEx, ATEX, UL, and CSA certifications in a single model, making it easier for global customers to standardize across plants in multiple world areas. Other certifications available include NEPSI, KOSHA, InMetro, and GOST.

Valvetop D-Series discrete valve controllers can survive in virtually any plant condition. Their heavy-duty construction and corrosion resistance enable superior performance in the most demanding applications.

The Valvetop D-Series is Built Tough!

Designed to provide reliable service for a lifetime, the Valvetop D-Series has been built to last in the most demanding applications, and endurance tested for over 3.5 million cycles to prove it.



Wet

Tested against intense water pressure blasts and complete submersion underwater for ½ hour



Hot

Tested for endurance in temperatures up to 176°F/80°C



Cold

Tested for endurance in temperatures down to -58°F/-50°C

Dirty

Tested in dust chamber and proven dust tight

Abusive

Tested against the "300 pound man step test" and proven impact and step resistant

Corrosive

Tested against hundreds of corrosive and caustic elements and proven to resist deterioration or chipping

Explosive

Tested by UL for use in explosive environments with no seal-off fittings required (DXP, DXS)

Chemical Compatibility

Tested against hundreds of chemicals with varying exposure times, temperatures, and concentrations. Please visit www.topworx.com for specific chemical compatibility information.



"I like the fact that the D-Series has world wide approvals since we have projects throughout the world."

- Project Engineer, Global Engineering Firm



Visual Display

- Impact resistant polycarbonate
- Intuitive colors (Green/Red)
- Adjustable/customizable
- Pre-adjusted to 90° for easy installation
- Less than 1 3/4" tall

Bus Networking / Sensor options

- FOUNDATION, DeviceNet, AS-Interface, HART
- GO™ Switch, Proximity, P+F™, Mechanical, 4-20mA Transmitter

Stainless Steel Shaft & Fasteners

- 1/4" DD or NAMUR Shaft
- Captive cover bolts
- Captive dome screws



Rugged Enclosures for every environment

- Aluminum, Composite, Stainless
- Up to four conduit entries (English or Metric)
- O-ring seals everywhere
- Buna, Viton, EPDM, Silicone o-ring options

Pilot Valves

- Aluminum, 304, 316 Stainless Steel available
- Low Power Solenoid or Ultra-Low Power Piezo
- Single or Dual Coil
- 1.2 Cv or 3.0 Cv
- Integrally mounted for extra protection
- Built-in, 5-micron filter protects the pilots against debris
- Fast, easy troubleshooting:
 - Pneumatic tubing is color-coded for trouble shooting while system is pressurized
 - Troubleshoot valve without removing the cover

Environmental extremes

- Operating temperatures from -58°F/-50°C to 176°F/80°C
- NEMA Type 4, 4X, 7 plus IP67

MULTIPLE D-SERIES PLATFORMS FOR EVERY ENVIRONMENT



DXP

Tropicalized Aluminum
Flameproof/Explosion Proof/Intrinsically Safe
Class I Division 1 Groups A-D
Class I Division 2 Groups A-D
Ex ia IIC T4 Tamb
-40°C to 55°C I12GD
Ex d IIB+H2 T6 Tamb
-50°C to +60°C I12GD
Ex d IIC T6 Tamb
-50°C to +60°C I12GD



DXS

316L Stainless Steel
Flameproof/Explosion Proof
/Intrinsically Safe
Class I Division 1 Groups A-D
Class I Division 2 Groups A-D
Ex ia IIC T4 Tamb
-40°C to 55°C I12GD
Ex d IIC T6 Tamb
-50°C to +60°C I12GD
Ex d IIB+H2 T6 Tamb
-50°C to +60°C I12GD

SIL-3
IEC 61508



D-ESD

Partial Stroke Testing for
Emergency Shutdown Valves
Suitable for use in SIL-3 applications
Stainless, Aluminum, or Resin
Flameproof/Explosion Proof
/Non-Incendive
Class I Division 1 Groups C & D
Class I Division 2 Groups A-D
Ex d IIB+H2 T6 Tamb -50°C
to +60°C I12GD



DXR

Composite Resin
Non-Incendive/Intrinsically Safe
Class I Division 2 Groups A-D
Class II Division 2 Groups F & G
Ex ia IIC T4 Tamb
-20°C to 53°C I12GD
Ex me [ia] IIC Tamb
-20°C to 44°C T4 I12G

VALVETOP™ T-SERIES


High-Value Switchboxes with a Variety of Options

Valvetop T-Series switchboxes deliver outstanding value by providing full functionality in compact, direct-mount enclosures.

Available with a variety of position sensors, integral solenoid valves, and bus networks, the T-Series is suitable for use in all hazardous areas and carry IECEx, ATEX, and CSA certifications.

The Valvetop T-Series Delivers Outstanding Value!

Designed to provide maximum functionality in a compact form factor, the Valvetop T-Series has a number of unique features that save space, time, and money.



Optimum Use of Space


The unique layout supplies ample working space inside the enclosure for wiring and setting of the switches while taking up very little space above the actuator.



TwistSet™ Cams


Unique TwistSet cam design allows easy access and accurate stepless setting of sensor position with minimum hysteresis.

Color-coded strikers enable quick identification of open/closed switches.



Low Profile Design

The unique direct-mounting feature eliminates expensive mounting brackets while reducing the height of the switchbox and the overall footprint above the actuator.



Direct Mounting

Unique mounting design enables simple attachment to any ISO/NAMUR actuator without the need for expensive mounting brackets



"I like the features of the T-Series products. The direct mount feature saves money on the cost of brackets."

- President, Valve Distributor



Solid Enclosures for Every Environment

- Aluminum, Composite, Stainless
- Up to four conduit entries (English or Metric)
- O-ring seals everywhere
- Buna, EPDM, O-ring options

Environmental Extremes

- Operating temperatures from -40°F/-40°C to 176°F/80°C
- NEMA 4, 4X

Pilot Valves

- Low Power Solenoid
- Single Coil
- 1.0 Cv
- Integrally mounted for extra protection



Visual Display

- Impact resistant polycarbonate
- Intuitive colors (Green/Red)
- Pre-adjusted to 90° for easy installation
- Low profile/High visibility
- Customizable

Bus Networking / Sensor Options

- AS-Interface, Profibus, DeviceNet
- GO Switch, Proximity, P+F, Mechanical


Stainless Steel Shaft and Fasteners

- NAMUR Shaft
- Captive cover bolts and indicator screws

MULTIPLE T-SERIES PLATFORMS FOR EVERY ENVIRONMENT



TVA | Direct-Mount Composite Resin
Intrinsically Safe
General Purpose
Ex ia IIC T4 II2G
Tamb -40° to 60°C



TXP | Direct-Mount Aluminum
Flameproof/Intrinsically Safe/
Explosion Proof /Non-Incendive
Class I Division 2 Groups A-D
Class I Division 1 Groups C & D
Class II Division 1 Groups E-G
Ex ia IIC T4 Tamb -50° to 85°C II2GD
Ex d IIB T4 Tamb -50° to 80°C II2GD
Ex d IIC T4 Tamb -50°C to 80°C II2GD



TXS | Direct-Mount Stainless Steel
Flameproof/Intrinsically Safe/
Explosion Proof /Non-Incendive
Class I Division 2 Groups A-D
Class I Division 1 Groups C & D
Class II Division 1 Groups E-G
Ex ia IIC T4 Tamb -50° to 85°C II2GD
Ex d IIB T4 Tamb -50° to 80°C II2GD
Ex d IIC T4 Tamb -50°C to 80°C II2GD

VALVETOP™ BUS NETWORKS

Connectivity to Every Fieldbus Network

SENSOR-COMMUNICATION MODULES

TopWorx Sensor-Communication Modules are microprocessor based 'brains' that mount inside Valvetop enclosures to deliver position sensing and bus networking functionality to on/off valves. They combine position sensors, bus communications, solenoid outputs, and wiring terminals into a compact, sealed module that drops into various Valvetop enclosures.

SCM Features:

- Short-circuit protection
- Resistant to impact, moisture, shock, vibration, contamination
- LEDs indicate valve position and facilitate sensor set-up




BUS NETWORKS


TopWorx Sensor-Communication Modules make it easy to connect automated on/off valves to modern bus networking protocols such as FOUNDATION Fieldbus, DeviceNet, AS-interface, Profibus, and HART.




DeviceNet



FOUNDATION Fieldbus




ASi



DeviceNet



T-Block





FOUNDATION FIELDBUS

- 5 Discrete Inputs, 3 Discrete Outputs
- Emerson DeltaV, Honeywell, Yokogawa, Rockwell, Invensys approved
- Pre-defined templates, on-board diagnostics, and early warning LEDs
- Consumes only 17mA to operate, reduces VCRs and DSTs required
- Local calibration button for factory setting of end of stroke switches
- Position feedback via DO read back reduces number of function blocks.

BEST-IN-CLASS CAPABILITIES

- Reduced number of blocks scheduled on the segment
- Reduced macrocycle times
- Reduced VCR Links (Publisher/Subscriber)
- Reduced DST count
- Higher density of valves per segment
- Less segments required per project (less hardware)
- Pre-Built and Industry Tested Library Modules (reduced engineering)
- Lower Total Cost of Ownership for Intrinsically Safe Applications

SINGLE DO BLOCK

Using the Readback function in the DO block for position feedback reduces the number of DSTs required and allows the user to switch the solenoid and get position feedback via this single DO block.

CALIBRATION SWITCH

The SCM-FF is equipped with a local calibration button for pre-installation function testing of the valve actuator package. This ensures that all valve automators can function test packages before installation without having to purchase expensive test equipment. LEDs indicate correct position setting of the switches.

PIEZO TECHNOLOGY

TopWorx discrete valve controllers incorporate the best piezo technology available on the market today. With a response time of under 50mS and a high flow rate, we ensure the spool valve reacts immediately to a change in signal.

DeviceNet

- 3 Discrete Inputs, 2 Discrete Outputs, 1 Analog Input
- Rockwell, Emerson DeltaV approved
- On-board diagnostics and early warning LEDs



- ASi 2.1 with up to 4 Discrete Inputs and 3 Discrete Outputs
- Early warning LEDs



- Profibus DP V0
- 4 Discrete Inputs
- 2 Discrete Outputs
- Early warning LEDs



- Digital confirmation of analog signal
- Auto-calibration via handheld



VALVETOP™ POSITION SENSORS

The Industry's Leading Selection of Position Sensors

Valvetop™ provides the industry's leading selection of valve position sensors, including GO™ Switch leverless limit switches, proximity sensors, mechanical limit switches, potentiometers, and 4-20mA position transmitters.

SENSORS & SWITCHES

- GO™ Switch leverless limit switches
- 4-20mA position transmitters with HART protocol
- Proximity
- Reed
- Mechanical

GO™ SWITCH INSIDE



GO™ Switch leverless limit switches are hermetically sealed and outperform all other position sensors in hot, cold, wet, dirty, abusive, corrosive, and explosive conditions. GO Switches deliver best-in-class capabilities:

- Highest amp rating (4amp/120vac, 3amp/24vdc)
- Highest temperature rating - 80°C
- Up to four GO Switches inside
- Hermetically Sealed contacts
- SPDT, DPDT, and Stainless Steel options
- Proximity operation – nothing to jam, bend, break, or wear out
- Resistant to electrical noise, radio frequency interference, dust, dirt, and most chemicals
- No leakage current, not voltage or polarity sensitive
- Simple device – inherently intrinsically safe with barrier
- Unlike Reed Switches, Gold flashed contacts allow for use in both low and high current applications within a single switch



PUSHSET CAM

Unique pushset cam design allows quick and accurate setting of the GO Switch positions reducing deadband and hysteresis to a minimum. Switches




can easily be set in the mid-position for control applications such as 3-way ball valves or diverter valves.



4-20mA POSITION TRANSMITTER



- Fully potted electronic module with LEDs and Auto Calibration feature
- Precise setting of the zero and span can be done in seconds for both CW and CCW rotation with a simple push button
- Position feedback sensor is mounted directly to the switchbox shaft eliminating backlash caused by traditional gear train
- Up to 300° rotation for choke valve applications
- The need for re-calibration is eliminated
- Available with GO Switches and HART Protocol



PROXIMITY SENSORS

Choose from a variety of proximity sensors including reed switches and inductive proximity sensors such as Pepperl+Fuchs™ and others.

- Up to 6 proximity sensors
- AC, DC, Namur versions available



MECHANICAL LIMIT SWITCHES

- Up to 6 mechanical switches
- 15A/120vac
- SPDT and DPDT contacts available
- Up to 6 mechanical switches

PNEUMATIC SWITCHES

- Common in marine/shipbuilding industry
- Ideal for explosive or intrinsically safe environments

Valvetop provides a portfolio of self-contained pilot valves to control pneumatic actuators. These compact, high flow spool valves are all low power and can deliver significant operating cost savings. Integral pilot valve options include solenoid and piezo pilots, aluminum and 316 or 304 stainless steel valve bodies, and pushbutton or palm actuated manual overrides.

SOLENOID VALVES

- 24Vdc, 120vac, 220vac
- Aluminum, 316 Stainless, 304 Stainless
- Single Coil, Dual Coil, Blocked Center
- High Flow up to 3.0Cv
- Low Power Consumption (solenoid 0.5 watts; piezo 12mw)
- Low temperature rating -50°C (-58°F) (on request)



PILOTS

- Internally mounted for protection from the environment
- Low Power Solenoid or Ultra-Low Power Piezo pilots
- Single or Dual Pilots
- Fail open, Fail closed, Fail in last position
- 50 million cycle minimum life
- Class F coil insulation (Class H available on request)
- Response time 10mS



VALVE BODIES

- Anodized Aluminum
- 316 Stainless Steel
- 304 Stainless Steel

Flow Rates

- 1.2 Cv
- 3.0 Cv



MANUAL OVERRIDES

- Momentary
- Latching
- Manual Reset
 - Prevents accidental opening of a tripped ESD valve
 - Local operator intervention is required before valve can be re-opened



DUAL VALVE

- Two integral solenoid valves configured in series or parallel
- For applications where a redundant solenoid is required
- For ESD valves or control of 3-position actuators




MANUAL RESET SOLENOID VALVE

- Designed for Critical Service or Emergency Shutdown Valve applications which often require operators to manually verify a system prior to restarting a process
- Features a 1.2 Cv flow rate and rugged 316 stainless steel housing, ideal for offshore applications

How It Works

- The pushbutton on the Manual Reset solenoid valve is manually pushed and latched. The inward movement of the pushbutton causes the valve to shift.
- The pilot is then energized, which unlatches the manual pushbutton, but does not change the valve state.
- When the coil is de-energized, the valve is returned to its original fail-safe mode.



FLAME ARRESTORS

These double as in line filters, protecting the pilot against damage caused by dirty air. This design also allows the users to replace or work on the external valve in situ without affecting the integrity of the explosion proof enclosure.

VALVETOP™ D-ESD

SIL-3 Partial Stroke Test Solutions

TopWorx SIL-3 ESD Valve Controllers provide a complete Partial Stroke Test Solution with unique features and functionality that enable partial stroke testing of emergency shutdown valves without disrupting or shutting down the process.

The **TopWorx Partial Stroke Test Solution** comes complete with:

- Sensor Control Module to partially close the valve without disrupting the process
- Pass/Fail indication via high/low response on the return signal
- Open and Closed position sensors for feedback to the DCS or PLC
- Onboard Diagnostics to enable predictive maintenance and early-warning alerts
- Aluminum, Composite, and 316L Stainless Steel platforms certified for use in Flameproof/Explosion Proof, or Non-Incendive hazardous areas
- An optional local, lockable partial stroke Test Button integral to the unit

The **TopWorx Partial Stroke Test Solution** provides Onboard Diagnostics to alert the user to the following Dangerous Failures:


- Valve packing/shaft damage
- Actuator spring fatigue/breakage
- Solenoid pilot exhaust blockage
- Solenoid spring failure



Convenient Partial Stroke Testing


Partial Stroke Test Module

GO™ Switch
Partial Stroke Confirmation Switch



Integral Solenoid

Spool Valve



Available in two platforms suitable for your particular application:



DXP | Tropicalized Aluminum
Flameproof/Explosion Proof



DXS | 316L Stainless Steel
Flameproof/Explosion Proof

SIL-3
IEC 61508



Capabilities

- Suitable for use in SIL-3 applications
- Certified for use in all hazardous areas
- Integrated solution with all controls in a single housing
- Onboard diagnostics for performance validation

TOPWORX™ 4310

Wireless Valve Position Monitor

More Monitoring Points

The TopWorx™ 4310 Wireless Position Monitor is a component of Emerson's Smart Wireless solutions for field instrumentation. Smart Wireless extends PlantWeb's predictive intelligence into areas that were previously out of physical or economic reach, opening the door for new possibilities in process management. The TopWorx 4310 Wireless Position Monitor sends a wireless feedback signal through the Gateway to indicate valve position, device temperature, and power module status. This non-obtrusive position monitor won't disrupt your existing process and is easy to overlay. The 4310 can be used to monitor equipment such as process valves, regulators, and displacement and float level sensors.

Ease of Use

Specially designed for the wireless monitoring of open/closed position in linear and rotary valves, no conduit easements or permits are needed for the battery-powered TopWorx 4310 Wireless Position Monitor. This reduces the time needed for installation, setup, and commissioning. The non-contact linkage-less design and multi-language local user interface allows for easy calibration and monitoring. The TopWorx 4310 Wireless Position Monitor is compact, simple to use, and easily mounted on various valves from modulating control to automated quarter-turn or manual. Emerson's Smart Wireless solutions are very scalable. Users can start small and add devices later, improving the network reliability. The more wireless devices on a network, the more reliable the network will become.

Rugged and Reliable

The TopWorx 4310 Wireless Position Monitor delivers scalable functionality in a small package. Its rugged, engineered resin enclosure and variety of hazardous area certifications make the 4310 a perfect solution for most applications, including those in corrosive or remote environments. The 4310 Wireless Position Monitor is a component of a self-organizing network that is not hindered by obstacles and disruptions. With frequency hopping technologies and redundant paths for information to travel along, the network delivers greater than 99% data reliability. Anti-jamming technology with 128-bit AES encryption, key rotation, authentication, and verification protects the data to give you peace of mind.

Safe and Cost Effective

The TopWorx 4310 Wireless Position Monitor installs quickly with no wiring or conduit of any kind, reducing not only the cost of installation but safety risks, monitoring time, and labor. Sites that present potential human safety risks may now be monitored easily from a safe location.



AMS® Suite:
Intelligent Device Manager

Omni-directional
antenna

WirelessHART
Communication
Protocol

TOPWORX

PARTIAL

Long life
power module

WirelessHART™ Diagnostics:

- Cycle counter
- Configuration
- Alerts
- Power Status



Modbus or OPC
access to device
variable information



Control System



Engineered
resin housing



Intrinsically
safe design



WirelessHART™ self-organizing network

How many devices can be on a single Wireless Gateway?

Up to 100.

How many hosts can communicate with a Wireless Gateway?

Many at the same time. For example: Legacy host systems (PLCs, DCS) and AMS® Device Manager.

Can you have more than one network?

Yes, for example when separating areas by function or location.

What is the maximum spacing between wireless devices?

75m is typical inside buildings, 200m is typical outside.

VALVETOP™ APPLICATIONS

Valve Control Solutions for Every Application

4-20mA TRANSMITTERS WITH HART PROTOCOL



The 2-wire position transmitter with HART will generate a nominal 4-20mA signal proportional to valve position output for full-range actuation of the valve. The transmitter is capable of generating signals below 4mA and above 20mA if the position sensor indicates an out-of-range value. With the added HART digital communication capability, remote calibration and parameter configuration can be performed via a handheld.

Features:

- Remote set point calibration using a handheld device for calibration and monitoring
- Selectable over and under travel settings
- 4 to 20mA variable reading
- Monitoring and setting of alarms with advanced diagnostics. Includes deadband detection, out of range indication and detection of internal memory errors



THE STAINLESS STEEL, 35-SERIES GO™ SWITCH

Hermetically-Sealed, Stainless Steel, DPDT Proximity Switch


For over fifty years, GO™ Switch position sensors have set the standard for reliability and durability in the process industries. Their unique operating principle and best-in-class capabilities have made them the most specified switch in the world for demanding process applications.

TopWorx™ has once again improved on greatness.

The 35-Series GO™ Switch is now available in two versions: The original Single Pole Double Throw GO™ Switch or the stainless steel, Double Pole Double Throw, version.

Features:

- One-piece, stainless steel housing
- Hermetically-sealed, Double Pole Double Throw contacts
- Suitable for both Ex d and Intrinsically Safe applications
- Up to four (4) switches in a single enclosure
- Extremely low hysteresis
- PLC and higher current ratings with AC/DC - NO/NC wiring flexibility
- 3amp/120vac and 1amp/24vdc
- Available with SOV and HART options



LINEAR VALVE MONITORS & SENSORS

Valvetop discrete valve controllers are the products of choice for linear valves of all types. Their precision sensing and proven reliability deliver the best position feedback available. Options such as 4-20mA transmitters with end-of-stroke sensors and HART protocol provide continuous monitoring and confirmation of valve position. Custom mounting kits are available to ensure reliable operation for the life of the valve package.



Valvetop D-Series on linear control valves

DXP WITH IEC/ATEX IIC CERTIFICATION

The Only IIC Valve Controller with an Integral Solenoid.


Most ATEX EEx d IIC valve controllers have small containers with screw-top lids and very few options. Often the threads on the screw-top lids bind up, causing safety issues on multiple levels. TopWorx™ is changing all of that with the IIC-certified DXP valve controller.

There is no competition.

The unique modular design of the Valvetop™ DXP discrete valve controller combines bus networking, pilot valve and position sensors into a globally certified, explosion proof enclosure that attaches to any automated valve package.

Features:

- Serrated Flange (No binding of threads)
- Improved ingress protection
- IECEx, ATEX, & EEx d Group IIC
- The only IIC Box with integral solenoid
- Available with all Bus & Sensor options!




VALVETOP™ APPLICATIONS

Valve Control Solutions for Every Application

DUAL PILOT VALVE FOR DRIBBLE FEED CONTROL

By using a unique dual valve option, the solenoids can be configured to allow two stage closing of the valve for applications such as tank filling where the valve needs to be throttled to prevent overflowing.



MULTI-TURN MANUAL VALVE

Unique adaptor for fitting position monitors to rising stem and non-rising stem gate and globe valves



VALVETOP VISUAL INDICATORS

A variety of indicators to fit every application, including multiple color combinations such as Green/Red and Yellow/Black, plus three-way, 90° and 180° flow paths. Other languages are also available upon request.



COLD TEMP TO -50°C/-58°F

The Valvetop D-Series operates at temperatures down to -50°C by using a special cold-temp solenoid configuration



“ We replaced all of a competitor’s switchbox with the TopWorx Valvetop using GO Switches. We can set the DXPs and walk away from them knowing that they work great. ”

- **I&C Leader**, Japanese Chemical Company



“ The TopWorx product was attractive to us because the enclosure was resilient and able to survive in a hazardous and corrosive environment. ”

- **Process Engineer**, German Chemical Company



VALVETOP™ MOUNTING KITS

VIP™ Brackets to Fit Any Rotary Valve or Actuator



VIP MOUNTING KIT

With over 1,500 mounting kit designs, Valvetop valve controllers can be mounted on any rack-n-pinion, scotch-yoke, or vane actuator, quarter-turn manual valves, linear knifegate and control valves, and positioners. Visit www.topworx.com for a complete list of available kits or to request a custom design.





TopWorx has thousands of mounting kits available to fit Valvetop and GO Switch products to a wide variety of valves and actuators. Each kit comes complete with parts list and installation instructions.

3Z Valve	Larox
Actreg	Ledeen
Airtorque	MAGNETROL
ANCHOR DARLING	Marwin
Apollo	Masoneilan
Automax	Mogas
AXELSON	Neles-Jamesbury
Baumann	Neway
Bettis	Newcon Valve
Biffi	Orbinox
Bray	Orbit
BROOKS BRODIE	PBM
Cameron	PBV
CCI	Poyam
ChemValve	Protech
Clarkson	PVC
Compaq	QTRCO
Conbraco	Radius
Contromatics	RCS
COPES VULCAN	Remote Control
Crane	RF Technologies
DeZurik	Rhino
Durco	Rotork
El-O-Matic	SAMSON
Fabri Valve	Severn Glocon
Fisher	SPEAKMAN
Flowbus	TBV
Flowserve	Triac
General Valve	Trutorq
Grinnell	Unitorq
HAWS	Valtek
HONEYWELL	Valvtechnologies
Hytork	Vanessa
ITT	Velan
KENNETH ELLIOT	VTI
Keystone-Morin	Watts
Kinetrol	WKM
Kitz	Worcester
KTM	Xomox-Matryx
KTM	



VALVETOP™ TECHNICAL INFORMATION

Dimensional Drawings, Electrical Ratings, Etc

D-SERIES DIAGRAMS





T-SERIES DIAGRAMS



DRY-CONTACT POSITION SENSORS



Electrical ratings:

- L (GO Switch): 4amp/120vac, 3amp/24vdc
- P (Hi-Amp Prox): 3amp/120vac, 2amp/24vdc
- R (Low-Amp Prox): .2amp/30vdc
- M (Mechanical Switch) 15A/120vac
- _X (4-20mA Transmitter) 8.5-34vdc



INDUCTIVE PROXIMITY SENSORS

- Available with all types of inductive proximity sensors, including Pepperl & Fuchs™, IFM™, and Turck™
- 3-Wire PNP/NPN:
 - : Voltage: 10-30vdc
 - : Power Consumption: 15mA
 - : Operating Current: 0- 200mA
- 2-Wire N/O & N/C
 - : Voltage: 5-250vac/vdc
 - : Power Consumption <0.5mA
 - : Operating Current: 0- 200mA
- Namur Output:
 - : 8vdc
 - : Current consumption:
 - : Switched: <1mA
 - : Unswitched: >3mA



SOLENOID VALVES

Pressure rating: 30-100psi (2 - 8 bar)

Temperature rating:



- Standard -20°C - +60°C
- Low Temp: -50°C to +60°C
- Standard Piezo: -20°C to +60°C
- Cold Temp. Piezo: -30°C to +60°C

Power consumption:

- Standard: 0.5Watts
- Piezo: 12mWatts

Voltages:

- 12/24vdc
- 110vac
- 220vac



VALVETOP™ ORDERING GUIDE

Choose one option from each category to build a complete model number.

Enclosure

D SERIES

✓ **DXP Tropicalized Aluminum**

✓ **DXR Composite Resin**
(*S* Silicone O-Rings only; Stainless steel conduit entries required for North American Approvals)

DXS 316L
Stainless steel

T SERIES

✓ **TXP Aluminum**

TXS 316 Stainless Steel

✓ **TVA Engineered Resin**
(Area Class must be W or 0)

Bus/Sensor

AS AS-Interface

(Area class cannot be 0)

✓ **FF FOUNDATION Fieldbus**
(D-Series only; Pilot P or R)

DN DeviceNet

(Area class cannot be 0)

PB Profibus DP (T-Series only;
Area class must be 1, C or W)

Partial Stroke Test

ES ESD/PST Module w/GO Switch
(D-Series only; Area class cannot be 0 or 2)

GO Switches

✓ **L2** (2)GO Switches SPDT hermetic seal

L4 (4)GO Switches SPDT hermetic seal
(D-Series only)

✓ **Z2** (2)GO Switches DPDT hermetic seal
(D-Series only)

Z4 (4)GO Switches DPDT hermetic seal
(D-Series only)

Mechanical Switches

(Area class cannot be 2)

✓ **M2** (2)Mech SPDT

M4 (4)Mech SPDT

M6 (6)Mech SPDT (D-Series only)

T2 (2)Mech DPDT

K2 (2)Mech SPDT gold contacts

K4 (4)Mech SPDT gold contacts

Proximity Switches

PN (2) SPDT Module w/o LED's, 1A max
(D-Series only)

PS (2) SPDT Module w/LED's, 250mA max
(D-Series only)

✓ **R2** (2) SPDT 250mA max
(T-Series only)

R4 (4) SPDT 250mA max
(T-Series only)

P2 (2) SPDT 3A max
(T-Series only)

Inductive Sensors

E2 (2) p+f NJ2+V3-N inductive NAMUR

E4 (4) p+f NJ2+V3-N inductive NAMUR
(D-Series only)

12 (2) Ind prox PNP N/O
(T-Series only Area class cannot be 0)

Analog Output

(Available with 2-switch options only for L,Z,M,K,E,T)

_X 4-20mA transmitter

_H 4-20mA transmitter
with HART
(Not available with switch option T)

Area Classification

D SERIES

✓ **0** Intrinsically safe
(Bus/sensor cannot be AS, DN, ES, or _X; Requires appropriate I.S. barrier)
- North America
Class I Div 1&2
Grps A, B, C, D
Type 4, 4X
- ATEX/IECEX
Zone 0
II1G, II2D, II2GD
Ex ia IIC
Ex tb IIIC, Db IP6X
(IP67 for DXP/S and IP64 for DXR)

✓ **1** Explosion proof/Flame proof (DXP/S only)
- North America
Class I Div 1&2 Grps C, D
Class I Div 2 Grps A, B, C, D
(Groups A & B must be hermetically sealed)
Type 4, 4X, 7
- ATEX/IECEX
Zone 1
II2G, II2GD
Ex d IIB+H2
Ex tb IIIC Db, IP67
(O-Rings must be S or E for DUST certification)

✓ **2** Non-incendive
(Bus/sensor must be L, Z, P, AS, FF or DN)
- North America
(DXR Only)
Class I Div 2
Grps A, B, C, D;
Class II Div 2 Grps F,G
- ATEX (DXP/S only)
II3G Ex nC tD, IP67
(O-Rings must be S or E for DUST certification)

G General Purpose (DXR only)
Type 4, 4X

C Flameproof (DXP only; Conduit entries must be E or M)
ATEX/IECEX II2G, II2GD
Ex d IIC Ex tb IIIC Db, IP67

W No approvals
IP67 for DXP/S
IP64 for DXR

T SERIES

0 Intrinsically safe
ATEX Zone 1 II2GD Ex ia IIC
Ex tb A21, IP67 (TXP/S only)
II2G Ex ia IIC, T4 (TVA only)

C Flame Proof (TXP & TXS w/o pilot valve only)
ATEX/IECEX II2GD Ex d IIC
Ex tD A21, IP67

✓ **1** Flame proof/Explosion Proof (TXP / TXS only)
- North America
Class I Div 1 Grps C, D
Class I Div 2 Grps A-D
Class II Grps E, F, G
Type 4X, IP 67
- ATEX/IECEX
Zone 1
II2GD Ex d IIB & IIC
Ex tD A21, IP67

✓ **2** Non-incendive (TXP/TXS only)
CI I Div 2 Grps A-D
CI II Div 2 Grps F&G
ATEX II3GD (Not available with all sensing options)
Ex nA IIC, IP67; Ex tD

G cCSAus General Purpose (TXP/TXS only)

✓ **W** No approvals
Nema 4, 4x IP67

Visual Display

✓ **G** Standard 90°
Green OPEN,
Red CLOSED

B 90°
Black OPEN,
Yellow CLOSED

Y 90°
Yellow OPEN
Black CLOSED

J 3 Way T Port,
Green/Red
(T-Series only)

K 3 Way L Port,
Green/Red
(T-Series only)

1 3 way, 90°
(D-Series only)

3 3 way, 90°
(D-Series only)

5 3 way, 90°
(D-Series only)

7 3 way, 180°
(D-Series only)

9 3 way, 180°
(D-Series only)

F Flat-top w/ skirt
indicator
(TXP/TXS only)

Ordering

Guide Fill in each box to create a complete model number.

Enclosure

Bus/Sensor

Area Classification

Visual Display

Ordering Examples:
DXP-FF0GNEBPA2
DXP-L21GNEB1A2
TXP-M21GNPB1A1

 **TopWorx preferred options.**

Shaft	Conduit	O-Rings	Pilot	Spool	Valve Cv	Override	Regional Certs
<p>✓ S 1/4" DD 304 SS (D-Series only)</p> <p>✓ N NAMUR 304 SS</p> <p>L 1" Extended Linear Shaft (TXP/TXS w/ Visual Display F only)</p> <p>R 1/4" DD 316 SS (Shaft & external hardware) (D-Series Only)</p> <p>M NAMUR 316 stainless steel (Shaft & external hardware) (D-Series Only)</p>	<p>DXP/DXS ✓ E (2) 3/4" NPT</p> <p>4 (2) 3/4" NPT (2) 1/2" NPT</p> <p>M (2) M20</p> <p>3 (4) M20</p> <p>6 (4) 3/4" NPT</p> <p>DXR (Stainless Conduit Entries)</p> <p>P (2) 1/2" NPT</p> <p>E (2) 3/4" NPT</p> <p>M (2) M20</p> <p>DXR (Resin Conduit Entries)</p> <p>A (2) 1/2" NPT</p> <p>B (2) 3/4" NPT</p> <p>C (2) M20</p> <hr/> <p>T SERIES</p> <p>TXP/TXS P (2) 1/2" NPT</p> <p>M (2) M20</p> <p>E (2) 3/4" NPT (N/A with Pilot Valve)</p> <p>3 (4) M20 (N/A with Pilot Valve)</p> <p>4 (2) 3/4" NPT (2) 1/2" NPT (N/A with Pilot Valve)</p> <p>TVA A (2) 1/2" NPT Resin (TVA only)</p> <p>C (2) M20 Resin (TVA only)</p>	<p>✓ D SERIES B Buna-N</p> <p>E EPDM</p> <p>S Silicone</p> <p>V Viton</p> <hr/> <p>T SERIES M Buna/EPDM mix (TVA) Silicone (TXP/TXS)</p>	<p>✓ Blank No pilot devices</p> <p>✓ 1 (1) 24Vdc pilot, .5W, fail open/ closed</p> <p>2 (2) 24Vdc pilot, .5W, fail last position (D Series Only)</p> <p>4 (1) 220vac pilot, 1.9W fail open/ closed</p> <p>5 (1) 220vac pilot, 1.9W fail last position (D Series Only)</p> <p>7 (1) 110vac pilot, 1.1W fail open/ closed</p> <p>8 (2) 110vac pilot, 1.1W fail last position (D Series Only)</p> <p>P (1) piezo pilot, fail open/ closed (FF only) (D Series only)</p> <p>R (2) piezo pilots, fail last position (FF only) (D Series only)</p>	<p>✓ Blank No spool valve</p> <p>✓ A Aluminum hard coat anodized</p> <p>S 304 SS (D Series Only)</p> <p>✓ 6 316 SS</p>	<p>✓ Blank No spool valve</p> <p>✓ 1 1.0 Cv (1/4" NPT Ports) (T Series Only)</p> <p>✓ 2 1.2 Cv (1/4" NPT ports) (D Series Only)</p> <p>3 3.0 Cv (D Series Only) (1/2" NPT ports)</p> <p>C Cold Temp valve 1.0 Cv (1/4" NPT Ports) (D-Series Only) (Sensors L2 and Z2, Pilot must be 1 or 2; Sensor FF, Pilot must be P or R)(O-Ring E or S only; Spool Valve S or 6 only) Bus/sensor L or Z = -50°C Bus/sensor FF = -30°C</p> <p>8 1.0 Cv (1/4" BSP Ports) (T-Series Only)</p>	<p>(All manual override options EXCEPT Option 1 are for D Series only)</p> <p>✓ Blank No override</p> <p>1 Single Pushbutton Momentary/Latching</p> <p>2 Dual Pushbutton Momentary/Latching</p> <p>3 Single Pushbutton Momentary</p> <p>4 Dual Pushbutton Momentary</p> <p>5 Manual Reset No voltage release latching with pushbutton (Consult factory if used with ES sensor option) (Spool valve must be 6)</p> <p>A Single palm actuator Momentary/Latching</p> <p>B Dual palm actuator Momentary/Latching</p> <p>C Single palm actuator Momentary</p> <p>D Dual palm actuator Momentary</p> <p>E Manual Reset No voltage release latching with palm actuator (Consult factory if used with ES sensor option) (Spool valve must be 6)</p> <p>T Partial stroke test button with lockable cover (Sensor ES only) (Not avail w/ Area Class C) (DXP/S - Conduit Entries 4 or 3 only, DXR - consult factory)</p>	<p>Blank No Regional Cert</p> <p>B InMetro (DXP/S only)</p> <p>N NEPSI</p> <p>R GOST (Cannot be DXR or TVA)</p> <p>F FISCO (D-Series Only) (Bus/Sensor must be FF; Area Class must be 0)</p> <p>K KOSHA</p>
Shaft	Conduit	O-Rings	Pilot	Spool	Valve Cv	Override	Regional Certs

GLOBAL SUPPORT OFFICES

Americas

3300 Fern Valley Road
Louisville, Kentucky 40213 USA
+1 502 969 8000
info.topworx@emerson.com

Asia-Pacific

1 Pandan Crescent
Singapore 128461
+65 6891 7550
info.topworx@emerson.com

Europe

Horsefield Way
Bredbury Industrial Estate
Stockport SK6 2SU
England
+44(0)161 406 5155
info.topworx@emerson.com

Middle East

P.O. Box 17033
Jebel Ali Free Zone
Dubai 17033
United Arab Emirates
+9714 8118283
info.topworx@emerson.com

Africa

2 Monteer Rd, Isando
Kempton Park
Gauteng, RSA
(27) 011 445 4475
info.topworx@emerson.com

Visit www.topworx.com for comprehensive information on our company, capabilities, and products – including model numbers, data sheets, specifications, dimensions, and certifications.

info.topworx@emerson.com

www.topworx.com

© 2011 TopWorx, Inc. All rights reserved. TopWorx, Valvetop, GO Switch, VIP, and Leverless Limit Switch are all trademarks of TopWorx, Inc. All other marks are the property of their respective owners. Information herein – including product specifications – is subject to change without notice.



About Emerson Process Management

Emerson Process Management is a powerful, global, single source of process improvement technology and expertise. We help major companies in selected industries optimize their plants and processes to achieve higher quality, greater reliability and faster time to market, while steadily advancing productivity and profitability. We can build it - providing experienced project management, engineering and a single point of accountability for the entire instrumentation and automation system. We can connect it -- seamlessly integrating people and technology at every level of the process. We can improve it -- creating more efficient utilization of energy and raw materials. And we can sustain it -- producing greater reliability, month after month, year after year. From the field, to the plant, to the bottom line -- where performance is the question, Emerson is the answer.

TOPWORX

